

STRAIGHT STEEL ROUND POLE

Pole Shaft.

Pole shaft shall be weldable-grade, cold-rolled, commercial quality carbon steel tubing conforming to ASTM A500 Grade B. Tubing has minimum yield strength of 45,000 PSI. SSR includes ground Lug welded inside opposite of Hand Hole.

Options include 11G (.120) and 7G (.180).

Base Plate.

Steel Plate base is manufactured from hot rolled carbon steel conforming to ASTM-A36 or equivalent (36,000 PSI) 3/4" thick Steel for poles up to 20ft and 1" thick for poles 21ft to 30ft.

Powder Coating.

All poles are sandblast prior to painting, Powder coat is applied to a minimum of 3 millimeters and baked at 400 °F temperature.

SSR come with (3) three years warranty.

Anchor Bolts.

Anchor bolt Kit includes 4 L-Shaped Hot Dip Galvanized Bolts, each anchor bolt come with two galvanized nuts and washer per bolt, Anchor bolts meet or exceed a minimum of 36,000 PSI and conform to ASTM F1554 grade 36.

Base Cover, Hand Hole Cover and Pole Cap.

SSR come with Removable Pole Cap and Aluminum Base Cover, Powder Coated to match Pole. Cast Hand Hole Cover are provided with Internal bridge support and are powder coated to match pole.



SSR						
Model	Height	Size/Gauge	Base	Mounting	Finish	Options
SSR	10'	4" OD-11G (4120)	9" Bolt Circle (9BC) 12" Bolt Circle (12BC)	No Drilling (ND)	Bronze (BZ)	Galvanize (G) GFI Provision (GFI) No Anchor Bolts (LAB) Marine Grade (MG)
	12'			Single (S)		
	15'	4" OD-7G (4180)	Double 180° (D180)	Dark Bronze (DBZ)		
	18'		Triple 90° (T)			
	20'	5" OD-11G (5120)	Quads 90° (Q)	White (WH)		
	25'		Tenon 2-3/8" (T238)	Silver (SLR)		
	30'		Tenon 2-3/4" (T234)	Green (GN)		
		Tenon 3" (T3)	Black (BK)			
		Tenon 2-1/2" (T312)	Graphite (GPH)			
		Tenon 4-1/2" (T412)	Custom (CST)			
		Tenon 5-1/2" (T512)				

POLE EPA

Maximum EPA (ft) allowance

Height	Pole Dia.	Thickness	Base Plate	Bolt Circle	Bolts	90 mph	100 mph	110 mph	120 mph	130 mph	140 mph
8'	3" OD.	11G	3/4" X 9" SQ	9.00"	3/4" X 24"	14.2	11.2	10.4	8.6	7.2	6.0
10'	3" OD.	11G	3/4" X 9" SQ	9.00"	3/4" X 24"	10.8	8.5	7.8	6.4	5.2	4.3
10'	4" OD.	11G	3/4" X 9" SQ	9.00"	3/4" X 24"	20.8	16.6	15.2	12.6	10.4	8.8
12'	3" OD.	11G	3/4" X 9" SQ	9.00"	3/4" X 24"	8.4	6.6	6.0	4.8	3.8	3.0
12'	4" OD.	11G	3/4" X 9" SQ	9.00"	3/4" X 24"	16.6	13.0	12	9.8	8.0	6.8
14'	3" OD.	11G	3/4" X 9" SQ	9.00"	3/4" X 24"	6.8	5.1	4.6	3.6	2.8	2.0
14'	4" OD.	11G	3/4" X 9" SQ	9.00"	3/4" X 24"	13.4	10.4	9.6	7.6	6.2	5.1
16'	3" OD.	11G	3/4" X 9" SQ	9.00"	3/4" X 24"	5.4	4.0	3.6	2.7	1.9	1.3
16'	4" OD.	11G	3/4" X 9" SQ	9.00"	3/4" X 24"	11.0	8.4	7.6	6.0	4.6	3.8
18'	3" OD.	11G	3/4" X 9" SQ	9.00"	3/4" X 24"	4.2	2.9	2.6	1.8	1.1	-
18'	4" OD.	11G	3/4" X 9" SQ	9.00"	3/4" X 24"	9.0	6.6	6.0	4.5	3.4	2.7
20'	4" OD.	11G	3/4" X 9" SQ	9.00"	3/4" X 24"	7.2	5.2	4.6	3.3	2.3	1.6
20'	5" OD.	11G	1" X 12" SQ	12.00"	3/4" X 24"	12.5	9.4	8.8	7.1	5.9	4.9
20'	5" OD.	7G	1" X 12" SQ	12.00"	1" X 36"	20.6	15.8	14.6	12.2	10.2	8.6
22'	4" OD.	7G	3/4" X 9" SQ	9.00"	3/4" X 24"	15.5	10.1	9.9	6.0	5.1	3.4
22'	5" OD.	7G	1" X 12" SQ	12.00"	1" X 36"	19.4	14.2	13.1	11.0	9.1	7.2
25'	4" OD.	7G	3/4" X 9" SQ	9.00"	3/4" X 24"	3.8	2.3	1.9	.08	-	-
25'	5" OD.	11G	1" X 12" SQ	12.00"	1" X 36"	7.6	5.2	4.7	3.7	2.9	2.2
25'	5" OD.	7G	1" X 12" SQ	12.00"	1" X 36"	13.4	9.8	9.	7.4	6.0	5.0
30'	5" OD.	11G	1" X 12" SQ	12.00"	1" X 36"	4.0	2.1	1.8	1.2	-	-
30'	5" OD.	7G	1" X 12" SQ	12.00"	1" X 36"	8.6	5.8	5.2	4.0	3.2	2.4

