

# STRAIGHT ALUM. ROUND POLE

- **SHAFT:** Straight aluminum 6063 alloy extrusion. Internal welding pole shaft to base.
- **WALL:** .125" .188" and .250" Gauge aluminum.
- **BASE:** Aluminum 10'-20' poles at 3/4" thickness. 22' & over at 1" thickness.
- 9'-12' bolt circle. 4 bolt pattern
- **ANCHOR BOLTS:** Hot dipped galvanized. 3/4" x 30" 4" J hook. 1" x 36" - 4" J hook.
- **FINISH:** 3 to 5 mils powder coat finish. Galvanized available upon request.
- **HAND HOLE:** included
- **POLE CAP:** included
- **CUSTOM BOLT CIRCLE:** no anchor bolts provided
- **TEMPLATE:** available with anchor bolts



MODEL	HEIGHT	SIZE / GAUGE	BASE	MOUNT	FINISH	OPTIONS
SAR	10'	4125 - 4" OD .125G (10-15' Poles Only)	9BC - 9" Bolt Circle	NOD - No Drill	BZ - Bronze	G - Galvanize
	12'	4188 - 4" OD .188G	12BC - 12" Bolt Circle (39' Only)	S - Single	DBRZ - Dark Bronze	GFI - GFI Provision
	15'	4250 - 4" OD .250G		D180 - Double 180°	BLK - Black	LAB - No Anchor Bolts
	18'	5188 - 5" OD .188G	D90 - Double 90°	WH - White	MG - Marine Grade Paint	
	20'	5250 - 5" OD .250G (25' & 30' Poles Only)	T - Triple 90°	SLV - Silver	RBP - Round Base Plate	
	25'		Q - Quads 90°			
	30'		T238 - Tenon 2-3/8"			
		T234 - Tenon 2-3/4"				
		T3 - Tenon 3"				
		T312 - Tenon 3-1/2"				
		T412 - Tenon 4-1/2"				
		T512 - Tenon 5-1/2"				

PROJECT NAME:

## FEATURES & SPECIFICATIONS

MODEL	NOMINAL HEIGHT	SIZE / THICKNESS	EPA 80MPH	EPA 90MPH	EPA 100MPH	BOLT CIRCLE	ANCHOR BOLTS
SAR104125	10	4"OD / .125"g	8	5.9	4.5	9	3/4x30 + 4
SAR124125	12	4"OD / .125"g	5.8	4.1	3	9	3/4x30 + 4
SAR154125	15	4"OD / .125"g	2.8	1.6	1	9	3/4x30 + 4
SAR154188	15	4"OD / .188"g	9.5	7.4	5.5	9	3/4x30 + 4
SAR184188	18	4"OD / .188"g	6.1	3.5	1.6	9	3/4x30 + 4
SAR120188	20	4"OD / .188"g	9.6	6.9	3.4	9	3/4x30 + 4
SAR205188	20	5"OD / .188"g	12.3	8.4	5.2	9	3/4x30 + 4
SAR255188	25	5"OD / .188"g	10.2	9.3	6.8	12	1x36 + 4

