

STEEL ROUND TAPERED POLE

- **SHAFT:** Hot rolled steel
Conforms to ASTM A500
standards. Rated at
55,000 PSI
- **WALL:** 120" 11 Gauge,
180" 7 Gauge
- **BASE:** ASTM-A36
standards. Manufactured
from A36 Steel rated at
36,000 PSI, 12' - 15' bolt
circle. 4 bolt pattern
- **ANCHOR BOLTS:** Hot
dipped galvanized.
1" x 36" - 4" J hook.
- **FINISH:** 3 to 5 mils
powder coat finish.
Galvanized available
upon request.
- **HAND HOLE:** included
- **POLE CAP:** included
- **CUSTOM BOLT CIRCLE:**
no anchor bolts provided
- **TEMPLATE:** available
with anchor bolts



MODEL	HEIGHT	GAUGE	BASE	MOUNT	FINISH	OPTIONS
SRT	20'	120 - 11G	12BC - 12" Bolt Circle	NOD - No Drill	BZ - Bronze	G - Galvanize
	25'	180 - 7G	15BC - 15" Bolt Circle (39' Only)	S - Single	DBRZ - Dark Bronze	GFI - GFI Provision
	30'			D180 - Double 180°	BLK - Black	LAB - No Anchor Bolts
	39'			D90 - Double 90°	WH - White	MG - Marine Grade Paint
				T - Triple 90°	SLV - Silver	RBP - Round Base Plate
				Q - Quads 90°		
				T238 - Tenon 2-3/8"		
				T234 - Tenon 2-3/4"		
				T3 - Tenon 3"		
				T312 - Tenon 3-1/2"		
				T412 - Tenon 4-1/2"		

PROJECT NAME:

FEATURES & SPECIFICATIONS

MODEL	NOMINAL HEIGHT	SIZE / THICKNESS	EPA 90MPH	EPA 100MPH	EPA 110MPH	BOLT CIRCLE	ANCHOR BOLTS
SRT20120	20	6.0 - 3.0 120"	20	15.1	14.5	12	1x 36 + 4
SRT20180	20	6.0 - 3.0 180"	31.1	27.2	24.1	12	1x 36 + 4
SRT25120	25	7.0 - 3.5 120"	19.8	14.3	13.8	12	1x 36 + 4
SRT25180	25	7.0 - 3.5 180"	32.1	25.5	25.7	12	1x 36 + 4
SRT30120	30	8.0 - 3.75 120"	11.5	10.1	8.5	12	1x 36 + 4
SRT30180	30	8.0 - 3.75 180"	28.5	24.5	17.5	12	1x 36 + 4
SRT39120	39	9.0 - 3.5 120"	10.3	8.7	7.4	12	1x 36 + 4
SRT39180	39	9.0 - 3-5 180"	21	19.1	16.2	12	1x 36 + 4

