

STRAIGHT STEEL ROUND POLE

- **SHAFT:** Straight steel grade B extrusion with yield 46,000 PSI conforms to ASTM A50 internal welding pole shaft to base
- **WALL:** 120" 11 Gauge, 180" 7 Gauge
- **BASE:** ASTM-A36 standards. Manufactured from A36 Steel rated at 36,000 PSI, 9' - 12' bolt circle. 4 bolt pattern
- **ANCHOR BOLTS:** Hot dipped galvanized. 3/4" x 30" 4" J hook. 1" x 36" - 4" J hook.
- **FINISH:** 3 to 5 mils powder coat finish. Galvanized available upon request.
- **HAND HOLE:** included
- **POLE CAP:** included
- **CUSTOM BOLT CIRCLE:** no anchor bolts provided
- **TEMPLATE:** available with anchor bolts



MODEL	HEIGHT	SIZE / GAUGE	BASE	MOUNT	FINISH	OPTIONS
SSR	10'	4120 - 4" OD 11G	9BC - 9" Bolt Circle	NOD - No Drill	BZ - Bronze	G - Galvanize
	12'	4180 - 4" OD 7G	12BC - 12" Bolt Circle	S - Single	DBRZ - Dark Bronze	GFI - GFI Provision
	15'	5120 - 5" OD 11G		D180 - Double 180°		BLK - Black
	18'	5180 - 5" OD 7G	D90 - Double 90°	WH - White	MG - Marine Grade Paint	
	20'		T - Triple 90°	SLV - Silver	RBP - Round Base Plate	
	25'		Q - Quads 90°			
	30'		T238 - Tenon 2-3/8"			
		T234 - Tenon 2-3/4"				
		T3 - Tenon 3"				
		T312 - Tenon 3-1/2"				
		T412 - Tenon 4-1/2"				
		T512 - Tenon 5-1/2"				

PROJECT NAME:

FEATURES & SPECIFICATIONS

MODEL	NOMINAL HEIGHT	SIZE / THICKNESS	EPA 90MPH	EPA 100MPH	EPA 110MPH	BOLT CIRCLE	ANCHOR BOLTS
SSR104120	10	4"OD/120" 11g	15.6	12.4	10.2	9	3/4x30 + 4
SSR124120	12	4"OD/120" 11g	13.9	10.6	8.7	9	3/4x30 + 4
SSR154120	15	4"OD/120" 11g	9	6.6	5.2	9	3/4x30 + 4
SSR184120	18	4"OD/120" 11g	7.2	5.1	3.9	9	3/4x30 + 4
SSR204120	20	4"OD/120" 11g	8	5.3	3.8	9	3/4x30 + 4
SSR204180	20	4"OD/180" 7g	5.9	4	2.9	9	3/4x30 + 4
SSR254120	25	4"OD/120" 11g	3.1	1.7	NA	12	1x 36 + 4
SSR254180	25	4"OD/180" 7g	6.1	4	2.7	12	1x36 + 4
SSR205120	20	5"OD/120" 11g	9.2	6.5	3.2	12	3/4x30 + 4
SSR205180	20	5"OD/180" 7g	18.2	13.4	9.5	12	3/4x30 + 4
SSR255120	25	5"OD/120" 11g	6.1	3.8	2.5	12	1x36 + 4
SSR255180	25	5"OD/180" 7g	12.2	8.5	6	12	1x36 + 4
SSR305120	30	5"OD/120" 11g	3.2	1.5	NA	12	1x36 + 4
SSR305180	30	5"OD/ 180" 7g	7	4.4	3.2	12	1x36 + 4

